According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus S5 V42P 2.5

Version	Revision Date:	SDS Number:	Date of last issue: 03.11.2022
2.11	30.03.2023	800001006674	Print Date 31.03.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name	: Shell Gadus S5 V42P 2.5
Product code	: 001D8525

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the Sub- stance/Mixture	: Automotive and industrial grease.
Uses advised against	: This product must not be used in applications other than those listed in Section 1 without first seeking the advice of the sup- plier.

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier	: Jungent Latvia AS Antonijas iela 24-9 LV-1010 Rīga Latvia
Telephone	: (+371) 673 65295
Telefax	:
Contact for Safety Data Sheet	: latvia@jungent.eu

1.4 Emergency telephone number

: 112

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)					
Long-term (chronic) aquatic hazard, Cat-	H412: Harmful to aquatic life with long lasting ef-				
egory 3	fects.				

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)				
Hazard pictograms Signal word		No Hazard Symbol required No signal word		
Hazard statements	:	PHYSICAL HAZARDS: Not classified as a physical hazard according to CLP		

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus S5 V42P 2.5

Version 2.11	Revision Date: 30.03.2023	SDS Num 80000100		Date of last issue: 03.11.2022 Print Date 31.03.2023	
		criteria H412	HEALTH H Not classif ENVIRON	IAZARDS: ied as a health hazard under CLP criteria. MENTAL HAZARDS: aquatic life with long lasting effects.	
Precautionary statements :		: Prevention: P273 Avoid release to the environment.			
		Respo		tionary phrases.	
		Storag		tionary phrases.	
		Dispos P501 dispos		contents/ container to an approved waste	
Sensi	tising components		iins Zinc Na produce an a	phthenate allergic reaction.	

2.3 Other hazards

This mixture does not contain any REACH registered substances that are assessed to be a PBT or a vPvB.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Prolonged or repeated skin contact without proper cleaning can clog the pores of the skin resulting in disorders such as oil acne/folliculitis.

Used grease may contain harmful impurities.

High-pressure injection under the skin may cause serious damage including local necrosis. Not classified as flammable but will burn.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical nature : A lubricating grease containing severely hydrotreated slack wax and additives.

Components

Chemical name	CAS-No. EC-No. Index-No.	Classification	Concentration (% w/w)
	Registration number		

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus S5 V42P 2.5

ersion 11	Revision Date: 30.03.2023		Number: 001006674		of last issue: 03.11.2022 Date 31.03.2023	2
	ates (Fischer - Tropsch /, C18-50 – branched, / near		848301-69-9 482-220-0 01-000002016	3-82	Asp. Tox. 1; H304	60 - 70
Napht	thenic acids, zinc salts,	, basic	84418-50-8 282-762-6 01-211998850	0-34	Skin Sens. 1B; H317 Eye Irrit. 2; H319 Aquatic Chronic 2; H411	0,1 - 0,9
Zinc c	oxide		1314-13-2 215-222-5 030-013-00-7 01-211946388	1-32	Aquatic Acute 1; H400 Aquatic Chronic 1; H410	0,25 - 0,9
					M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	
Alkary	/I amine		68411-46-1 270-128-1 01-211949129	9-23	Repr. 2; H361	0,1 - 0,9

For explanation of abbreviations see section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

Protection of first-aiders	:	When administering first aid, ensure that you are wearing the appropriate personal protective equipment according to the incident, injury and surroundings.
If inhaled	:	No treatment necessary under normal conditions of use. If symptoms persist, obtain medical advice.
In case of skin contact	:	Remove contaminated clothing. Flush exposed area with wa- ter and follow by washing with soap if available. If persistent irritation occurs, obtain medical attention.
		When using high pressure equipment, injection of product under the skin can occur. If high pressure injuries occur, the casualty should be sent immediately to a hospital. Do not wait for symptoms to develop. Obtain medical attention even in the absence of apparent wounds.
In case of eye contact	:	Flush eye with copious quantities of water. Remove contact lenses, if present and easy to do. Continue rinsing. If persistent irritation occurs, obtain medical attention.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus S5 V42P 2.5

Vers 2.11	ion	Revision Date: 30.03.2023	-	S Number: 0001006674	Date of last issue: 03.11.2022 Print Date 31.03.2023
	lf swalld	owed	:	In general no treatment is necessary unless large quantities are swallowed, however, get medical advice.	
4.2 N	lost im	portant symptoms ar	nd e	ffects, both acute	and delayed
	Sympto	ms	:	of black pustules a Ingestion may rest Local necrosis is e	signs and symptoms may include formation and spots on the skin of exposed areas. ult in nausea, vomiting and/or diarrhoea. evidenced by delayed onset of pain and ew hours following injection.
				5	5,
4.3 li	ndicatio	on of any immediate i	ned	ical attention and	special treatment needed
	Treatme	-	:	Notes to doctor/ph Treat symptomatic High pressure injevention and possib age and loss of fur Because entry woo ousness of the und determine the external anaesthetics or ho can contribute to s surgical decompre- eign material shou	ysician: cally. ction injuries require prompt surgical inter- bly steroid therapy, to minimise tissue dam-
SEC		5: Firefighting meas	sure	es	
5.1 E	Extingui	shing media			
	Suitable	e extinguishing media	:		/ or fog. Dry chemical powder, carbon diox- may be used for small fires only.
	Unsuita media	ble extinguishing	:	Do not use water i	n a jet.
5.2 S	Special	hazards arising from	the	substance or mix	ture

Specific hazards during fire- fighting	:	Hazardous combustion products may include: A complex mixture of airborne solid and liquid particulates and gases (smoke). Carbon monoxide may be evolved if incomplete combustion occurs. Unidentified organic and inorganic compounds.

5.3 Advice for firefighters

Special protective equipment for firefighters	:	Proper protective equipment including chemical resistant gloves are to be worn; chemical resistant suit is indicated if large contact with spilled product is expected. Self-Contained
		Breathing Apparatus must be worn when approaching a fire in

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus S5 V42P 2.5

Version 2.11	Revision Date: 30.03.2023		DS Number: 00001006674	Date of last issue: 03.11.2022 Print Date 31.03.2023
				. Select fire fighter's clothing approved to ls (e.g. Europe: EN469).
Specif ods	ic extinguishing meth-	:	0 0	measures that are appropriate to local cir- the surrounding environment.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions	 6.1.1 For non emergency personnel: Avoid contact with skin and eyes. 6.1.2 For emergency responders: Avoid contact with skin and eyes.
----------------------	---

6.2 Environmental precautions

Environmental precautions	:	Use appropriate containment to avoid environmental contami- nation. Prevent from spreading or entering drains, ditches or rivers by using sand, earth, or other appropriate barriers.

6.3 Methods and material for containment and cleaning up

Methods for cleaning up : Shovel into a suitable clearly marked container for disposal or reclamation in accordance with local regulations.

6.4 Reference to other sections

For guidance on selection of personal protective equipment see Section 8 of this Safety Data Sheet., For guidance on disposal of spilled material see Section 13 of this Safety Data Sheet.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Technical measures	:	Use local exhaust ventilation if there is risk of inhalation of vapours, mists or aerosols. Use the information in this data sheet as input to a risk assessment of local circumstances to help determine appropriate controls for safe handling, storage and disposal of this material.
Advice on safe handling	:	Avoid prolonged or repeated contact with skin. Avoid inhaling vapour and/or mists. When handling product in drums, safety footwear should be worn and proper handling equipment should be used. Properly dispose of any contaminated rags or cleaning mate- rials in order to prevent fires.

7.2 Conditions for safe storage, including any incompatibilities

Further information on stor-	:	Keep container tightly closed and in a cool, well-ventilated
age stability		place.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus S5 V42P 2.5

Version 2.11	Revision Date: 30.03.2023		0S Number: 0001006674	Date of last issue: 03.11.2022 Print Date 31.03.2023
			Use properly labe Store at ambient t	led and closable containers. emperature.
Packag	ing material	:	ering the packagir	
Contair	ner Advice	:		ainers should not be exposed to high tem- e of possible risk of distortion.
7.3 Specific Specific	: end use(s) c use(s)	:	Not applicable	

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
Oil mist, mineral	Not As- signed	AER 8 st	5 mg/m3	LV OEL
Oil mist, mineral		TWA (inhalable fraction)	5 mg/m3	US. ACGIH Threshold Limit Values
Oil mist, mineral		TWA	5 mg/m3	LV OEL

Biological occupational exposure limits

8.2 Exposure controls

Engineering measures

The level of protection and types of controls necessary will vary depending upon potential exposure conditions. Select controls based on a risk assessment of local circumstances. Appropriate measures include:

Adequate ventilation to control airborne concentrations.

Where material is heated, sprayed or mist formed, there is greater potential for airborne concentrations to be generated.

General Information:

Define procedures for safe handling and maintenance of controls.

Educate and train workers in the hazards and control measures relevant to normal activities associated with this product.

Ensure appropriate selection, testing and maintenance of equipment used to control exposure, e.g. personal protective equipment, local exhaust ventilation.

Drain down system prior to equipment break-in or maintenance.

Retain drain downs in sealed storage pending disposal or subsequent recycle.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus S5 V42P 2.5

Version	Revision Date:	SDS Number:	Date of last issue: 03.11.2022
2.11	30.03.2023	800001006674	Print Date 31.03.2023

Always observe good personal hygiene measures, such as washing hands after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Discard contaminated clothing and footwear that cannot be cleaned. Practice good housekeeping.

Due to the product's semi-solid consistency, generation of mists and dusts is unlikely to occur.

Personal protective equipment

The provided information is made in consideration of the PPE directive (Council Directive 89/686/EEC) and the CEN European Committee for Standardisation (CEN) standards.

Personal protective equipment (PPE) should meet recommended national standards. Check with PPE suppliers.

Eye protection	:	If material is handled such that it could be splashed into eyes, protective eyewear is recommended. Approved to EU Standard EN166.	
Hand protection			
Remarks	:	Where hand contact with the product may occur the use of gloves approved to relevant standards (e.g. Europe: EN374, US: F739) made from the following materials may provide suitable chemical protection. PVC, neoprene or nitrile rubber gloves Suitability and durability of a glove is dependent on usage, e.g. frequency and duration of contact, chemical resistance of glove material, dexterity. Always seek advice from glove suppliers. Contaminated gloves should be replaced. Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturizer is recommended. For continuous contact we recommend gloves with break-through time of more than 240 minutes with preference for > 480 minutes where suitable gloves can be identified. For short-term/splash protection we recommend the same but recognize that suitable gloves offering this level of protection may not be available and in this case a lower breakthrough time maybe acceptable so long as appropriate maintenance and replacement regimes are followed. Glove thickness is not a good predictor of glove resistance to a chemical as it is dependent on the exact composition of the glove material. Glove thickness should be typically greater than 0.35 mm depending on the glove make and model.	
Skin and body protection	:	Skin protection is not ordinarily required beyond standard work clothes. It is good practice to wear chemical resistant gloves.	
Respiratory protection	:	No respiratory protection is ordinarily required under normal conditions of use. In accordance with good industrial hygiene practices, precautions should be taken to avoid breathing of material.	

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus S5 V42P 2.5

Version	Revision Date: 30.03.2023	SDS Number:	Date of last issue: 03.11.2022
2.11		800001006674	Print Date 31.03.2023
		tions to a level select respirato cific conditions Check with resp Where air-filteri priate combinat Select a filter so and vapours [T	controls do not maintain airborne concentra- which is adequate to protect worker health, ory protection equipment suitable for the spe- of use and meeting relevant legislation. piratory protective equipment suppliers. ing respirators are suitable, select an appro- tion of mask and filter. uitable for combined particulate/organic gases ype A/Type P boiling point > 65°C (149°F)] 387 and EN143.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties					
Physical state	:	Semi-solid at ambient temperature.			
Colour	:	light brown			
Odour	:	Slight hydrocarbon			
Odour Threshold	:	Data not available			
Dropping point	:	180 °C Method: IP 396			
Melting / freezing point		Not applicable			
Initial boiling point and boiling range	:	Data not available			
Flammability					
Flammability (solid, gas)	:	Not applicable			
Flammability (liquids)	:	Not classified as flammable but will burn.			
Lower explosion limit and uppe	er ez	xplosion limit / flammability limit			
Upper explosion limit / upper flammability limit	:	Typical 10 %(V)			
Lower explosion limit / Lower flammability limit	:	Typical 1 %(V)			
Flash point	:	Not applicable			
Auto-ignition temperature	:	> 320 °C			
Decomposition temperature Decomposition tempera- ture	:	Data not available			

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus S5 V42P 2.5

Vers 2.11		Revision Date: 30.03.2023		S Number: 0001006674	Date of last issue: 03.11.2022 Print Date 31.03.2023
	pН		:	Not applicable	
	Viscosity Viscosity, dynamic		:	Data not availab	e
	Viso	cosity, kinematic	:	42 mm2/s (40,0 ^v Method: ASTM [
				8 mm2/s (100 °C Method: ASTM [
Solubility(ies) Water solubility			:	negligible	
	Solubility in other solvents			Data not availabl	e
	Partitio octano	n coefficient: n- l/water	:	log Pow: > 6 (based on inform	ation on similar products)
	Vapou	r pressure	: < 0,5 Pa (20 °C) estimated value(s)		s)
	Relativ	e density	:	0,900 (15 °C)	
Density		y	:	900 kg/m3 (15,0 Method: Unspec	
	Relativ	e vapour density	:	> 1 estimated value(s)
9.2 (Other in	nformation			
	Explos	ives	:	Classification Co	de: Not classified
	Oxidizi	ng properties	:	Data not availabl	e
	Flamm	ability (liquids)	:	Not classified as	flammable but will burn.
	Evapor	ration rate	:	Data not availabl	e
	Condu	ctivity	:	This material is r	not expected to be a static accumulator.

SECTION 10: Stability and reactivity

10.1 Reactivity

The product does not pose any further reactivity hazards in addition to those listed in the following sub-paragraph.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus S5 V42P 2.5

Version 2.11	Revision Date: 30.03.2023	SDS Number: 800001006674	Date of last issue: 03.11.2022 Print Date 31.03.2023
Stabl		xpected when handle	d and stored according to provisions
10.3 Poss	bility of hazardous	reactions	
Haza	rdous reactions	: Reacts with	strong oxidising agents.
10.4 Cond	ditions to avoid		
Cond	itions to avoid	: Extremes of	temperature and direct sunlight.
10.5 Inco	mpatible materials		
	rials to avoid	: Strong oxidis	ing agents.
	rdous decompositio	-	ed.
Inforr expos	nation on likely routes sure		contact are the primary routes of exposure alt- are may occur following accidental ingestion.
Acut	e toxicity		
Prod	uct:		
	e oral toxicity	: LD50 (rat): > Remarks: Lov Based on ava	
Acute	e inhalation toxicity	: Remarks: Bas are not met.	sed on available data, the classification criteria
Acute	e dermal toxicity	Remarks: Lov): > 5.000 mg/kg v toxicity ilable data, the classification criteria are not met.
Skin	corrosion/irritation		
<mark>Prod</mark> Rema			repeated skin contact without proper cleaning pores of the skin resulting in disorders such as oil

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus S5 V42P 2.5

rsion 1	Revision Date: 30.03.2023	-	9S Number: 0001006674	Date of last issue: 03.11.2022 Print Date 31.03.2023				
Serio	Serious eye damage/eye irritation							
<u>Produ</u>	uct:							
Remarks Respiratory or skin sensitisa		:	: Slightly irritating to the eye. Based on available data, the classification criteria are not met					
		satio	n					
Produ	uct:							
Rema	arks	:	Not a sensitise	and skin sensitisation: r. able data, the classification criteria are not me				
Germ cell mutagenicity <u>Product:</u>								
Geno	toxicity in vivo	:	Remarks: Non Based on avail	mutagenic able data, the classification criteria are not me				
Germ sessn	cell mutagenicity- As- nent	:	This product de categories 1A/	pes not meet the criteria for classification in 1B.				
Carci	nogenicity							
Produ	uct:							
Rema	ırks	:	Not a carcinog Based on avail	en. able data, the classification criteria are not me				
Carcir ment	nogenicity - Assess-	:	This product de categories 1A/	pes not meet the criteria for classification in 1B.				
Mater	rial	G	HS/CLP Carcin	ogenicity Classification				
Zinco	xide	N	o carcinogenicity	classification.				

Reproductive toxicity

Product: Effects on fertility		Remarks: Not a developmental toxicant., Does not impair fertility., Based on available data, the classification criteria ar not met.	
Reproductive toxicity - As- sessment	:	This product does not meet the criteria for classification in categories 1A/1B.	

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus S5 V42P 2.5

Version 2.11	Revision Date: 30.03.2023	SDS Number: 800001006674	Date of last issue: 03.11.2022 Print Date 31.03.2023
STO	Γ - single exposure		
<u>Prod</u> Rema		: Based on av	ailable data, the classification criteria are not met.
STO	Г - repeated exposure		
<u>Prod</u> Rema		: Based on av	ailable data, the classification criteria are not met.
Aspir	ration toxicity		
<u>Prod</u> Not a		ased on available o	data, the classification criteria are not met.
11.2 Infor	mation on other haza	rds	
Endo	ocrine disrupting prop	erties	
Prod	uct:		
Asse	ssment	ered to have REACH Artie	ce/mixture does not contain components consid- endocrine disrupting properties according to cle 57(f) or Commission Delegated regulation 100 or Commission Regulation (EU) 2018/605 at % or higher.
Furth	er information		
Prod	uct:		
Rema	arks	mulated duri ties will depe and the envi ALL used gr	e may contain harmful impurities that have accu- ng use. The concentration of such harmful impuri- end on use and they may present risks to health ronment on disposal. ease should be handled with caution and skin ded as far as possible.
Rema	arks		re injection of product into the skin may lead to a sif the product is not surgically removed.
Rema	arks	: Slightly irrita	ting to respiratory system.
Rema	arks	: Classificatio frameworks	ns by other authorities under varying regulatory may exist.
Rema	arks		ated otherwise, the data presented is representa- oduct as a whole, rather than for individual com-

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus S5 V42P 2.5

Version	Revision Date:	SDS Number:
2.11	30.03.2023	800001006674

Date of last issue: 03.11.2022 Print Date 31.03.2023

SECTION 12: Ecological information

12.1 Toxicity

	Product:		
	Toxicity to fish	:	Remarks: LL/EL/IL50 10-100 mg/l Harmful
	Toxicity to daphnia and other aquatic invertebrates	:	Remarks: LL/EL/IL50 10-100 mg/l Harmful
	Toxicity to algae/aquatic plants	:	Remarks: LL/EL/IL50 10-100 mg/l Harmful
	Toxicity to fish (Chronic tox- icity)	:	Remarks: Data not available
	Toxicity to daphnia and other : Remarks: Data not available aquatic invertebrates (Chron- ic toxicity)		Remarks: Data not available
	Toxicity to microorganisms	:	Remarks: Data not available
	Components:		
	Zinc oxide:		
	M-Factor (Acute aquatic tox- icity)	:	1
	M-Factor (Chronic aquatic toxicity)	:	1
12.	2 Persistence and degradabili	ity	
	Product:		
	Biodegradability	:	Remarks: Not readily biodegradable. Major constituents are inherently biodegradable, but contains com- ponents that may persist in the environment.
12.	3 Bioaccumulative potential		
	Product:		
	Bioaccumulation	:	Remarks: Contains components with the potential to bioaccumulate.
12.	4 Mobility in soil		
	Product:		
	Mobility	:	Remarks: Semi-solid under most environmental conditions., If

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus S5 V42P 2.5

Version 2.11	Revision Date: 30.03.2023	SDS Number: 800001006674	Date of last issue: 03.11.2022 Print Date 31.03.2023
it enters : bile.			l adsorb to soil particles and will not be mo-
		Remarks: Floats of	on water.
12.5 Result	s of PBT and vPvB as	ssessment	
<u>Produc</u> Assess			not contain any REACH registered sub- assessed to be a PBT or a vPvB
12.6 Endoc	rine disrupting prope	rties	
<u>Produc</u> Assess		have endocrine disr 57(f) or Commission	ure does not contain components considered to upting properties according to REACH Article on Delegated regulation (EU) 2017/2100 or ation (EU) 2018/605 at levels of 0.1% or higher.
12.7 Other	adverse effects		
Produc Additio mation	<u>et:</u> nal ecological infor-	tion potential or glo Product is a mixture	e depletion potential, photochemical ozone crea- bal warming potential. e of non-volatile components, which will not be y significant quantities under normal conditions
		Poorly soluble mixt Causes physical for	ture. Iling of aquatic organisms.
			herwise, the data presented is representative of ole, rather than for individual component(s).

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product	 Recover or recycle if possible. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste classification and disposal methods in compliance with applicable regulations. Do not dispose into the environment, in drains or in water courses.
	Waste product should not be allowed to contaminate soil or ground water, or be disposed of into the environment. Waste, spills or used product is dangerous waste.

Waste, spills or used product is dangerous waste. Waste arising from a spillage or tank cleaning should be dis-

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus S5 V42P 2.5

Version 2.11	Revision Date: 30.03.2023	SDS Number: 800001006674	Date of last issue: 03.11.2022 Print Date 31.03.2023
		to a recognis collector or o Do not dispo	accordance with prevailing regulations, preferably sed collector or contractor. The competence of the contractor should be established beforehand. use of tank water bottoms by allowing them to be ground. This will result in soil and groundwater on.
		Pollution from	see International Convention for the Prevention of m Ships (MARPOL 73/78) which provides tech- s at controlling pollutions from ships.
Contaminated packaging		to a recogniz the collector Disposal sho	ccordance with prevailing regulations, preferably zed collector or contractor. The competence of or contractor should be established beforehand. ould be in accordance with applicable regional, d local laws and regulations.
Local	legislation		
Wast	e catalogue	:	
		EU Waste D	isposal Code (EWC):
Wast	e Code	:	
		12 01 12*	
Rema	arks		buld be in accordance with applicable regional, d local laws and regulations.
		Classification user.	n of waste is always the responsibility of the end

SECTION 14: Transport information

14.1 UN number or ID number				
ADR	:	Not regulated as a dangerous good		
RID	:	Not regulated as a dangerous good		
IMDG IATA	:	Not regulated as a dangerous good Not regulated as a dangerous good		
14.2 UN proper shipping name				
ADR	:	Not regulated as a dangerous good		
RID	:	Not regulated as a dangerous good		
IMDG IATA	:	Not regulated as a dangerous good Not regulated as a dangerous good		

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus S5 V42P 2.5

Version 2.11	Revision Date: 30.03.2023	-	DS Number: 00001006674	Date of last issue: 03.11.2022 Print Date 31.03.2023	
14.3 Trans	sport hazard class(es)				
ADR		:	Not regulated as	a dangerous good	
RID		:	Not regulated as a	a dangerous good	
IMDG IATA		:	5	a dangerous good a dangerous good	
14.4 Packing group					
ADR		:	Not regulated as	a dangerous good	
RID		:	Not regulated as a	a dangerous good	
IMDG IATA		:		a dangerous good a dangerous good	
14.5 Envir	onmental hazards				
ADR		:	Not regulated as	a dangerous good	
RID		:	Not regulated as	a dangerous good	
IMDG		:	Not regulated as a	a dangerous good	
14.6 Speci	ial precautions for us	ər			
Rema	rks	:	for special precau	ns: Refer to Section 7, Handling & Storage, itions which a user needs to be aware of or with in connection with transport.	

14.7 Maritime transport in bulk according to IMO instruments

MARPOL Annex 1 rules apply for bulk shipments by sea.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)

: Not applicable

REACH - List of substances subject to authorisation (Annex XIV)

: Product is not subject to Authorisation under REACH.

Volatile organic compounds : Volatile organic compounds (VOC) content: 0 %

Other regulations:

The regulatory information is not intended to be comprehensive. Other regulations may apply to this material.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus S5 V42P 2.5

Version	Revision Date:	SDS Number:	Date of last issue: 03.11.2022		
2.11	30.03.2023	800001006674	Print Date 31.03.2023		
The components of this product are reported in the following inventories:					

The components of this pro-	uuc	are reported in the following inventiones
REACH	:	Notified with Restrictions.
TSCA	:	All components listed.

15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: Other information

Full text of H-Statements

H304 :	May be fatal if swallowed and enters airways.
H317 :	May cause an allergic skin reaction.
H319 :	Causes serious eye irritation.
H361 :	Suspected of damaging fertility or the unborn child.
H400 :	Very toxic to aquatic life.
H410 :	Very toxic to aquatic life with long lasting effects.
H411 :	Toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Aquatic Acute Aquatic Chronic Asp. Tox. Eye Irrit. Repr. Skin Sens. LV OEL		Short-term (acute) aquatic hazard Long-term (chronic) aquatic hazard Aspiration hazard Eye irritation Reproductive toxicity Skin sensitisation Latvia. Occupational exposure limit values
LV OEL	:	Latvia. Occupational exposure limit values
LV OEL / TWA		Time weighted average
LV OEL / AER 8 st	:	Limit value measured and calculated for an 8-hour period

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA -European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus S5 V42P 2.5

Version	Revision Date:	SDS Number:	Date of last issue: 03.11.2022
2.11	30.03.2023	800001006674	Print Date 31.03.2023

Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Training advice	:	Provide adequate information, instruction and training for op- erators.	
Other information :		A vertical bar () in the left margin indicates an amendment from the previous version.	
Sources of key data used to compile the Safety Data Sheet	:	The quoted data are from, but not limited to, one or more sources of information (e.g. toxicological data from Shell Health Services, material suppliers' data, CONCAWE, EU IUCLID date base, EC 1272 regulation, etc).	
Classification of the mixtur	e:	Classification procedure:	
Aquatic Chronic 3 H4		Expert judgement and weight of evi- dence determination.	
Identified Uses according to the Use Descriptor System Uses - Worker			
Title	:	General use of lubricants and greases in vehicles or machin- ery Industrial	
Uses - Worker			
Title			
	:	General use of lubricants and greases in vehicles or machin- ery Professional	
Uses - Worker Title	:	-	

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

LV / EN

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus S5 V42P 2.5

Version	Revision Date:	SDS Number:
2.11	30.03.2023	800001006674

Date of last issue: 03.11.2022 Print Date 31.03.2023

Exposure Scenario - Worker 30000000189

SECTION 1	EXPOSURE SCENARIO TITLE
Title	General use of lubricants and greases in vehicles or machin- ery Industrial
Use Descriptor	Sector of Use: SU3 Process Categories: PROC 1, PROC 2, PROC 8b, PROC 9 Environmental Release Categories: ERC4, ERC7, ATIEL- ATC SPERC 4.Bi.v1
Scope of process	Covers general use of lubricants and greases in vehicles or machinery in closed systems. Includes filling and draining of containers and operation of enclosed machinery (including engines) and associated maintenance and storage activities.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES	
Additional Information	No exposure assessment presented for human health.	

Section 2.1	Control of Worker Exposure
Product Characteristics	

Contributing Scenarios Risk Management Measures

Section 2.2	Control of Environmental Exposure	9	
Amounts Used			
EU tonnage (tonnes per year	2,63E+03		
Fraction of EU tonnage used	in region:	0,1	
Fraction of Regional tonnage	used locally:	0,1	
Frequency and Duration of	Use		
Emission Days (days/year):		300	
Environmental factors not i	nfluenced by risk management		
Local freshwater dilution factor	pr:	10	
Local marine water dilution fa	ctor:	100	
Other Operational Conditions affecting Environmental Exposure			
Negligible wastewater emissi	ons as process operates without water		
contact.			
Release fraction to air from p	5,00E-05		
Release fraction to wastewate	2,00E-11		
RMMs and before (municipal) sewage treatment plant):			
Release fraction to soil from process (after typical onsite RMMs):		0	
Technical conditions and measures at process level (source) to prevent release			
	ss sites thus conservative process re-		
lease estimates used.			
Technical onsite conditions and measures to reduce or limit discharges, air emis-			
sions and releases to soil			
Treat air emission to provide	a typical removal efficiency of (%)	70	

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus S5 V42P 2.5

Version	Revision Date:	SDS Number:	Date of last issue: 03.11.2022
2.11	30.03.2023	800001006674	Print Date 31.03.2023

Prevent discharge of undissolved substance to or recover from onsite	
wastewater.	
User sites are assumed to be provided with oil/water separators or	
equivalent and for waste water to be discharged via public sewer sys-	
tem. Organisational measures to prevent/limit release from site	
Do not apply industrial sludge to natural soils.	
Sludge should be incinerated, contained or reclaimed.	
Conditions and Measures related to municipal sewage treatment p	plant
Estimated substance removal from wastewater via domestic sewage	9,23E-02
treatment (%)	
Assumed domestic sewage treatment plant flow (m3/d)	2,00E+03
Maximum allowable site quantity (MSafe) based on OCs and RMMs as above (kg/day) :	2,634321E+06
Conditions and Measures related to external treatment of waste for	or disposal
External treatment and disposal of waste should comply with applicable regulations.	e local and/or regiona
Conditions and measures related to external recovery of waste	
External recovery and recycling of waste should comply with applicable regulations.	e local and/or regiona

SECTION 3

EXPOSURE ESTIMATION

Section 3.1 - Health

No exposure assessment presented for human health.

Section 3.2 - Environment

Used ECETOC TRA model.

SECTION 4

GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO

Section 4.1 - Health

No exposure assessment presented for human health.

Section 4.2 - Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Further details on scaling and control technologies are provided in SpERC factsheet (http://cefic.org).

If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a sitespecific chemical safety assessment is required.

For further information see www.ATIEL.org/REACH_GES.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus S5 V42P 2.5

Version	Revision Date:	SDS Number:
2.11	30.03.2023	800001006674

Date of last issue: 03.11.2022 Print Date 31.03.2023

Exposure Scenario - Worker 300000010651

SECTION 1	EXPOSURE SCENARIO TITLE
Title	General use of lubricants and greases in vehicles or machin- ery Professional
Use Descriptor	Sector of Use: SU22 Process Categories: PROC 1, PROC 2, PROC 8a, PROC 8b, PROC 20 Environmental Release Categories: ERC9a, ERC9b, ATIEL-ATC SPERC 9.Bp.v1
Scope of process	Covers general use of lubricants and greases in vehicles or machinery in closed systems. Includes filling and draining of containers and operation of enclosed machinery (including engines) and associated maintenance and storage activities.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
Additional Information	No exposure assessment presented for human health.

ction 2.1 C	ontrol of Worker Exposure
duct Characteristics	

Contributing Scenarios Risk Management Measures

Section 2.2	Control of Environmental Exposure	
Amounts Used		
EU tonnage (tonnes per year	r):	5.387,2
Fraction of EU tonnage used	in region:	0,1
Fraction of Regional tonnage	used locally:	0,1
Frequency and Duration of	Use	
Emission Days (days/year):		365
Environmental factors not	influenced by risk management	
Local freshwater dilution fact	or:	10
Local marine water dilution factor:		100
Other Operational Conditio	ns affecting Environmental Exposure)
Negligible wastewater emissi	ons as process operates without water	
contact.		
Release fraction to air from p	rocess (after typical onsite RMMs) :	
Release fraction to wastewater from process (after typical onsite		5,00E-04
RMMs and before (municipal) sewage treatment plant):		
Release fraction to soil from process (after typical onsite RMMs): 1E-03		1E-03
Technical conditions and n	neasures at process level (source) to	prevent release
Common practices vary acro	ss sites thus conservative process re-	
lease estimates used.		
Technical onsite conditions sions and releases to soil	s and measures to reduce or limit dis	charges, air emis-

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus S5 V42P 2.5

	Version 2.11	Revision Date: 30.03.2023	SDS Number: 800001006674	Date of last issue: 03.1 ⁺ Print Date 31.03.2023
--	-----------------	---------------------------	-----------------------------	--

Prevent discharge of undissolved substance to or recover from onsite	
wastewater.	
Organisational measures to prevent/limit release from site	
Do not apply industrial sludge to natural soils.	
Sludge should be incinerated, contained or reclaimed.	
Conditions and Measures related to municipal sewage treatment p	olant
Estimated substance removal from wastewater via domestic sewage treatment (%)	0,1
Assumed domestic sewage treatment plant flow (m3/d)	2,00E+03
Maximum allowable site quantity (MSafe) based on OCs and RMMs as above (kg/day) :	29.727
Conditions and Measures related to external treatment of waste for	r disposal
External treatment and disposal of waste should comply with applicable regulations.	e local and/or regional
Conditions and measures related to external recovery of waste	
External recovery and recycling of waste should comply with applicable	local and/or regional

1.2022

External recovery and recycling of waste should comply with applicable local and/or regional regulations.

SECTION 3

EXPOSURE ESTIMATION

Section 3.1 - Health

No exposure assessment presented for human health.

Section 3.2 - Environment

Used ECETOC TRA model.

SECTION 4

GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO

Section 4.1 - Health

No exposure assessment presented for human health.

Section 4.2 - Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Further details on scaling and control technologies are provided in SpERC factsheet (http://cefic.org).

If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a sitespecific chemical safety assessment is required.

For further information see www.ATIEL.org/REACH_GES.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus S5 V42P 2.5

Version	Revision Date:	SDS Number:	
2.11	30.03.2023	800001006674	I

Date of last issue: 03.11.2022 Print Date 31.03.2023

1

Exposure Scenario - Worker 300000010679

30000010073	
SECTION 1	EXPOSURE SCENARIO TITLE
Title	Use of lubricants and greases in open systems Industrial
Use Descriptor	Sector of Use: SU3 Process Categories: PROC 1, PROC 2, PROC 7, PROC 8b, PROC 9, PROC 10, PROC 13 Environmental Release Categories: ERC4, ATIEL-ATC SPERC 4.Ci.v1
Scope of process	Covers use of lubricants and greases in open systems, in- cluding application of lubricant to work pieces or equipment by dipping, brushing or spraying (without exposure to heat), e.g. mould releases, corrosion protection, slideways. Includes associated product storage, material transfers, sampling and maintenance activities.

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
Additional Information	No exposure assessment presented for human health.

Section 2.1	Control of Worker Exposure
Product Characteristics	

Contributing Scenarios Risk Management Measures

Section 2.2	Control of Environmental Exposure	1
Amounts Used	· · · · · · · · · · · · · · · · · · ·	
EU tonnage (tonnes per year	·):	380,9
Fraction of EU tonnage used	in region:	0,1
Fraction of Regional tonnage	used locally:	0,1
Frequency and Duration of	Use	
Emission Days (days/year):		300
Environmental factors not	influenced by risk management	
Local freshwater dilution fact	or:	10
Local marine water dilution fa	actor:	100
Other Operational Condition	ns affecting Environmental Exposure	;
Negligible wastewater emiss	ions as process operates without water	
contact.		
Release fraction to air from p	rocess (after typical onsite RMMs) :	5,00E-05
	er from process (after typical onsite	2,00E-11
RMMs and before (municipal) sewage treatment plant):	
	process (after typical onsite RMMs):	0
Technical conditions and n	neasures at process level (source) to	prevent release
	ss sites thus conservative process re-	
lease estimates used.		
Technical onsite condition	s and measures to reduce or limit dis	charges, air emis-

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus S5 V42P 2.5

Version	R
2.11	30

evision Date: 0.03.2023

SDS Number: 800001006674

Date of last issue: 03.11.2022 Print Date 31.03.2023

Treat air emission to provide a typical	removal efficiency of (%)	70
Prevent discharge of undissolved sub		10
wastewater.		
User sites are assumed to be provide	d with oil/water separators or	
equivalent and for waste water to be	•	
tem.	<u>j</u>	
Organisational measures to preven	t/limit release from site	
Do not apply industrial sludge to natu	ral soils.	
Sludge should be incinerated, contain	ed or reclaimed.	
Conditions and Measures related to	o municipal sewage treatment p	plant
Estimated substance removal from w	astewater via domestic sewage	0,1
treatment (%)		
Assumed domestic sewage treatmen	plant flow (m3/d)	2,00E+03
Maximum allowable site quantity (MS	afe) based on OCs and RMMs	386.082,9
as above (kg/day) :		
Conditions and Measures related to		
External treatment and disposal of wa	ste should comply with applicable	e local and/or regional
regulations.		
Conditions and measures related t		
External recovery and recycling of wa	ste should comply with applicable	e local and/or regional
regulations.		
SECTION 3 EXPO	SURE ESTIMATION	

No exposure assessment presented for human health.

Section 3.2 - Environment

Used ECETOC TRA model.

SECTION 4	GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO
Section 4.1 - Health	

No exposure assessment presented for human health.

Section 4.2 - Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Further details on scaling and control technologies are provided in SpERC factsheet (http://cefic.org).

If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a sitespecific chemical safety assessment is required.

For further information see www.ATIEL.org/REACH_GES.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus S5 V42P 2.5

Version	Revision Date:	SDS Number:	Date
2.11		800001006674	Print
2.11	30.03.2023	800001006674	Print

Date of last issue: 03.11.2022 Print Date 31.03.2023

Exposure Scenario - Worker 300000010680

SECTION 1	EXPOSURE SCENARIO TITLE	
Title	Use of lubricants and greases in open systems Professional	
Use Descriptor	Sector of Use: SU22 Process Categories: PROC 1, PROC 2, PROC 8a, PROC 10, PROC 11, PROC 13 Environmental Release Categories: ERC8a, ERC8d, ATIEL-ATC SPERC 8.Cp.v1	
Scope of process	Covers use of lubricants and greases in open systems, in- cluding application of lubricant to work pieces or equipment by dipping, brushing or spraying (without exposure to heat), e.g. mould releases, corrosion protection, slideways. Includes associated product storage, material transfers, sampling and maintenance activities.	

SECTION 2	OPERATIONAL CONDITIONS AND RISK MANAGEMENT MEASURES
Additional Information	No exposure assessment presented for human health.

Section 2.1	Control of Worker Exposure
Product Characteristics	

Contributing Scenarios Risk Management Measures

Section 2.2	Control of Environmental Exposure	
Amounts Used	·	
EU tonnage (tonnes per year):	224
Fraction of EU tonnage used	in region:	0,1
Fraction of Regional tonnage	used locally:	0,1
Frequency and Duration of	Use	
Emission Days (days/year):		365
Environmental factors not	influenced by risk management	
Local freshwater dilution factor	or:	10
Local marine water dilution fa	actor:	100
Other Operational Conditio	ns affecting Environmental Exposure)
Negligible wastewater emissi	ons as process operates without water	
contact.		
Release fraction to air from p	rocess (after typical onsite RMMs) :	
	er from process (after typical onsite	5,00E-04
RMMs and before (municipal		
	process (after typical onsite RMMs):	1E-03
Technical conditions and n	neasures at process level (source) to	prevent release
Common practices vary acro	ss sites thus conservative process re-	
lease estimates used.		
Technical onsite conditions	s and measures to reduce or limit dis	charges, air emis-

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus S5 V42P 2.5

Version	Revis
2.11	30.03

sion Date: 3.2023 SDS Number: 800001006674

Date of last issue: 03.11.2022 Print Date 31.03.2023

Prevent discharge of undissolved substance to or recover from onsite	
wastewater.	
Organisational measures to prevent/limit release from site	
Do not apply industrial sludge to natural soils.	
Sludge should be incinerated, contained or reclaimed.	
Conditions and Measures related to municipal sewage treatment p	plant
Estimated substance removal from wastewater via domestic sewage treatment (%)	0,1
Assumed domestic sewage treatment plant flow (m3/d)	2,00E+03
Maximum allowable site quantity (MSafe) based on OCs and RMMs as above (kg/day) :	3.443
Conditions and Measures related to external treatment of waste for	or disposal
External treatment and disposal of waste should comply with applicable regulations.	e local and/or regional
Conditions and measures related to external recovery of waste	
External recovery and recycling of waste should comply with applicable regulations.	e local and/or regional

SECTION 3

EXPOSURE ESTIMATION

Section 3.1 - Health

No exposure assessment presented for human health.

Section 3.2 - Environment

Used ECETOC TRA model.

SECTION 4

GUIDANCE TO CHECK COMPLIANCE WITH THE EXPOSURE SCENARIO

Section 4.1 - Health

No exposure assessment presented for human health.

Section 4.2 - Environment

Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures.

Further details on scaling and control technologies are provided in SpERC factsheet (http://cefic.org).

If scaling reveals a condition of unsafe use (i.e., RCRs > 1), additional RMMs or a sitespecific chemical safety assessment is required.

For further information see www.ATIEL.org/REACH_GES.

According to EC No 1907/2006 as amended as at the date of this SDS

Shell Gadus S5 V42P 2.5

Version Revision Date: 2.11 30.03.2023 SDS Number: 800001006674

Date of last issue: 03.11.2022 Print Date 31.03.2023